



“Oil” shall mean “used oil” as defined under 40 CFR 279, that is not characterized as hazardous waste under 40 CFR 261, and that complies with the Used Oil Acceptance Criteria as set forth in the table below.

USED OIL ACCEPTANCE CRITERIA*

Test	Test Method	Criteria		
		Min	Target	Max
Appearance	Visual check	--	Report	--
Density (g/ml - lb/gal)	D4052	--	Report	--
Water by Karl Fisher , % wt	ASTM D6304	--	5	15 **
Flash Point (PMCC), °F	ASTM D93	140	--	--
PCBs, ppm	GC-ECD	--	--	< 2
pH value	pH meter	--	Report	--
Phosphorus, ppm	ASTM D5185	--	--	1500
Sulfur, ppm	ASTM D5185	--	--	5500
Total Chlorine, ppm	ASTM D5185	--	--	1000 ***
Arsenic, ppm	ASTM D5185	--	--	5
Cadmium, ppm	ASTM D5185	--	--	2
Chromium, ppm	ASTM D5185	--	--	10
Lead, ppm	ASTM D5185	--	--	100
Silicon, ppm	ASTM D5185	--	100	250 ****
Vanadium, ppm	ASTM D5185	--	Report	--
Nickel, ppm	ASTM D5185	--	Report	--
Titanium, ppm	ASTM D5185	--	Report	--

UMO-BTAC01 - Revision : 03/01/2024

Notes:

- * - Used Oil as defined by 40 CFR Part 279 - Blue Tide Customer Profile Required
- ** - Criteria may be waived by Management on a case by case basis
- *** - If >1000 ppm Chlorine must pass rebuttable presumption per 40 CFR 279 (b)(1)(ii)
- **** - Criteria may be waived by Management on a case by case basis